



DUAL BUILT-IN CHARGER USB-A / USB-C™ WITH LED INDICATOR AND BUTTON

Always a full battery. The dual USB-A and USB-C™ charger can be installed in no time as a practical charging station - in motorhomes, caravans and boats.

When charging mobile devices such as smartphones, tablets and lights, the charger simultaneously indicates the on-board voltage. If no device is connected, the display can be activated at the push of a button.

FEATURES

- With USB-A and USB-C™ connection for quick and easy charging
- Charges popular smart phones at high speed with Quick Charge and Power Delivery
- Easy to install and compatible with Berker and Inprojal switch ranges
- Suitable for wall thicknesses up to 17 mm
- Safe due to rounded edges, protection against short circuits, overvoltage, high temperatures. Dust protection optional.
- With open cable ends
- Including 7-segment LED display for on-board voltage (automatic switch-off at 90 % battery charge)
- Push button that activates the status display for ca. 1 minute

DUAL BUILT-IN CHARGER USB-A / USB-C™ WITH LED INDICATOR AND BUTTON

PRODUCT



ITEM	65756
MODEL	WTS-E 2 A QC 3 PD-1 with LED-S
INSTALLATION	without connector
CABLE LENGTH	200 mm

TECHNICAL DATA

OUTPUT POWER	2 x 18 W
CURRENT IN STAND-BY MODE	5-7 mA
NOMINAL INPUT VOLTAGE	12-24 V \equiv
DIMENSIONS	Ø front: 36 mm, Ø installation: 27 mm, depth: 45.7 mm
WEIGHT	30 g
OPERATING TEMPERATURE	-20 °C - +80 °C
STORAGE TEMPERATURE	-40 °C - +90 °C
COMPATIBLE	with all current smartphones, tablets, rechargeable lamps, etc.
STANDARDS AND CERTIFICATIONS	CE, UKCA EN 55032:2015, EN 55035:2017, EN 50498:2011, EN IEC 62368-1:2020 RoHS, REACH ECE-R10 Type Approval FMVSS 201 (Compliance tests - Upper Interior Head Impact Protection)



CONNECTIONS AND FAST-CHARGING TECHNOLOGY

	USB-A 	USB-C™  Reversible Connector
TOTAL POWER	5.0 V \equiv max. 3.0 A (15 W) 9.0 V \equiv max. 2.0 A (18 W) 12.0 V \equiv max. 1.5 A (18 W)	5.0 V \equiv max. 3.0 A (15 W) 9.0 V \equiv max. 2.0 A (18 W) 12.0 V \equiv max. 1.5 A (18 W)
FAST-CHARGING TECHNOLOGY	QC 3.0, QC 2.0 FCP DCP BC 1.2 AFC SCP PE 2.0 PE 1.1 SFCP	PD 3.0 PPS QC 3.0 QC 4.0 QC 4+ AFC FCP BC 1.2 DCP SCP PE 2.0 PE 1.1 SFCP
LIFETIME IN INSERTION AND REMOVAL CYCLES	ca. 1,500	ca. 10,000